

MOOREBANK INTERMODAL TERMINAL

Annual Noise Review - April 2022 to April 2023

6 July 2023

QUBE c/o Tactical

TL116-05F21 Annual Review May 2023 (r2).docx

Document details

Detail	Reference
Doc reference:	TL116-05F21 Annual Review May 2023 (r2).docx
Prepared for:	QUBE c/o Tactical
Address:	Level 15, 124 Walker Street North Sydney, NSW, 2060
Attention:	

Document control

Date	Revision history	Non-issued revision	Issued revision	Prepared	Instructed	Reviewed / Authorised
23/06/2023	Draft	0	1		-	
6/07/2023	Final	-	2		-	

File Path: R:\AssocSydProjects\TL101-TL150\TL116 - cw Moorebank IMT Temporary Noise Monitoring\Task 5 - cw Operation Compliance Monitoring\1 Docs\Report 21 2023 Annual Review\TL116-05F21 Annual Review May 2023 (r2).docx

Important Disclaimers:

The work presented in this document was carried out in accordance with the Renzo Tonin & Associates Quality Assurance System, which is based on Australian/New Zealand Standard AS/NZS ISO 9001.

This document is issued subject to review and authorisation by the suitably qualified and experienced person named in the last column above. If no name appears, this document shall be considered as preliminary or draft only and no reliance shall be placed upon it other than for information to be verified later.

This document is prepared for the particular requirements of our Client referred to above in the 'Document details' which are based on a specific brief with limitations as agreed to with the Client. It is not intended for and should not be relied upon by a third party and no responsibility is undertaken to any third party without prior consent provided by Renzo Tonin & Associates. The information herein should not be reproduced, presented or reviewed except in full. Prior to passing on to a third party, the Client is to fully inform the third party of the specific brief and limitations associated with the commission.

In preparing this report, we have relied upon, and presumed accurate, any information (or confirmation of the absence thereof) provided by the Client and/or from other sources. Except as otherwise stated in the report, we have not attempted to verify the accuracy or completeness of any such information. If the information is subsequently determined to be false, inaccurate or incomplete then it is possible that our observations and conclusions as expressed in this report may change.

We have derived data in this report from information sourced from the Client (if any) and/or available in the public domain at the time or times outlined in this report. The passage of time, manifestation of latent conditions or impacts of future events may require further examination and re-evaluation of the data, findings, observations and conclusions expressed in this report.

We have prepared this report in accordance with the usual care and thoroughness of the consulting profession, for the sole purpose described above and by reference to applicable standards, guidelines, procedures and practices at the date of issue of this report. For the reasons outlined above, however, no other warranty or guarantee, whether expressed or implied, is made as to the data, observations and findings expressed in this report, to the extent permitted by law.

The information contained herein is for the purpose of acoustics only. No claims are made and no liability is accepted in respect of design and construction issues falling outside of the specialist field of acoustics engineering including and not limited to structural integrity, fire rating, architectural buildability and fit-for-purpose, waterproofing and the like. Supplementary professional advice should be sought in respect of these issues.

External cladding disclaimer: No claims are made and no liability is accepted in respect of any external wall and/or roof systems (eg facade / cladding materials, insulation etc) that are: (a) not compliant with or do not conform to any relevant non-acoustic legislation, regulation, standard, instructions or Building Codes; or (b) installed, applied, specified or utilised in such a manner that is not compliant with or does not conform to any relevant non-acoustic legislation, regulation, standard, instructions or Building Codes.

Contents

1	Introduction	1
1.1	Project overview	1
2	Compliance Matrix	2
3	Warehouse noise monitoring	9
4	Continuous noise monitoring in residential areas	10
5	Continuous rail link noise monitoring	11
5.1	Year 3 rail operations noise monitoring report	11
6	Rail link angle of attack (AoA) monitoring	15
6.1	Year 3 rail operations AoA monitoring	15
7	Noise monitoring in response to complaints	17
8	Other noise-related tasks	19
8.1	IMEX operations	19
8.2	Warehouse operations and Moorebank Noise Management Precinct	19
9	Conclusion	20
APPENDIX A	Glossary of terminology	21
APPENDIX B	Detailed noise assessment reports	26
B.1	Angle of Attack Monitoring Report - 1 December 2022 and 30 April 2023	27

List of tables

Table 1	Compliance matrix	3
---------	-------------------	---

List of figures

Figure 1	Measured $L_{Aeq(15\text{hour})}$ daytime noise levels at 30 m from track centreline	12
Figure 2	Measured $L_{Aeq(9\text{hour})}$ night-time noise levels at 30 m from track centreline	13
Figure 3	Measured L_{AFmax} daytime noise levels at 7.5 m from track centreline	13
Figure 4	Measured L_{AFmax} night-time noise levels at 7.5 m from track centreline	14
Figure 5	Maximum AoA value for each train - 1 December 2022 and 30 April 2023	16

1 Introduction

1.1 Project overview

The Sydney Intermodal Terminal Alliance (SIMTA) received approval for the construction and operation of Stages 1 and 2 of the Moorebank Precinct East (MPE) Project (SSD 6766 and SSD 7628 respectively), which together comprise the two stages of development under the MPE Concept Approval (MP10_0193).

This **Annual Noise Review** report **for Year 3 Operations (April 2022 to April 2023)** has been prepared to address the requirements of Approval Condition B90 of SSD 7628 as follows:

For the duration of operation, the Applicant must:

- a) continue to implement all reasonable and feasible best practice noise mitigation measures;*
- b) continue to investigate ways to reduce noise generated by the development, including maximum noise levels which may result in sleep disturbance; and*
- c) report on these investigations and the implementation and effectiveness of these measures in the Annual Review to the satisfaction of the Secretary.*

Table 1 provides a summary of the noise-related Approval Conditions and how these are addressed in this Annual Noise Review.

Appendix A contains a glossary of acoustic terms used in this report.

Appendix B contains a copy of the reports referred to in this report that are not publicly available on the SIMTA website.

2 Compliance Matrix

Table 1 provides a summary of the Approval Conditions which relate to operational noise emissions for Year 3 operations, and a discussion of the operational noise monitoring results. Where required, additional information is provided in later sections of this report or the appendices.

Table 1 Compliance matrix

Condition ID	Condition	Comments on compliance	Reference for further information
SSD 6766			
G7	The Applicant shall install and maintain a rail noise monitoring system on the rail link at the commencement of operation to continuously monitor the noise from rail operations on the rail link. The system shall capture the noise from each individual train passby noise generation event, and include information to identify: a) Time and date of freight train passbys; b) Imagery or video to enable identification of the rolling stock during day and night; c) $L_{Aeq(15\text{hour})}$ and $L_{Aeq(9\text{hour})}$ from rail operations; and d) $L_{AF(max)}$ and SEL of individual train passbys, measured in accordance with ISO3095; or e) Other alternative information as agreed with, or required by, the Secretary. The results from the noise monitoring system, shall be publicly accessible from a website maintained by the Applicant. The noise results from each train shall be available on the website within 24 hours of it passing the monitor, unless unforeseen circumstances (i.e. a system malfunction) have occurred. The $L_{Aeq(15\text{hour})}$ and $L_{Aeq(9\text{hr})}$ results from each day shall be available on the website within 24 hours of the period ending. Prior to the commencement of operation, the Applicant shall submit for the approval of the Secretary, justification supporting the appropriateness of the location for rail noise monitoring, including details of any alternative options considered and reasons for these being dismissed. The rail noise monitoring system shall not operate until the Secretary has approved the proposed monitoring location. The Applicant shall provide an annual report to the Secretary with the results of monitoring for a period of 5 years, or as otherwise agreed with the Secretary, from the commencement of operation of the IMEX terminal. The Secretary shall consider the need for further reporting following a review of the results for year 5.	The commencement of IMT operations occurred in May 2020. The new rail link was commissioned in November 2019. A description of the noise monitoring systems are provided in Section 5 and capture the information required by this approval. A Functional and Performance Specification for the permanent noise monitoring system and angle of attack monitoring system was prepared for approval by the Secretary before the rail link commissioning. A summary of the noise monitoring results for Year 3 operations is provided in Section 5.1.	https://moorebankintermodalprecinct.com.au/wp-content/uploads/2023/04/TJ741-04F04-AoA-and-Functional-Spec-for-Permanent-Noise-Monitor-r9_redacted.pdf https://moorebanknoisemonitor-emsbktrackiq.net/NoiseMonitor/ Section 5

Condition ID	Condition	Comments on compliance	Reference for further information						
G7A	The applicant shall install and maintain a wayside angle of attack monitoring system on the rail link at the commencement of operation to continuously monitor the angle of attack to the rail of rolling stock wheels. The system shall capture the angle of attack from a wheel on each axle of every train, and include information to identify: a) Time and date of each axle passby; and b) The identification number of each item of rolling stock. The results from the angle of attack monitoring system shall be: • accessible by train operators from a website maintained by the Applicant. Angle of attack results from each train shall be available on the website within 24 hours of it passing the monitor, unless unforeseen circumstances have occurred. • included in a six-monthly report to the Secretary. The report should at least identify the number of wagons with wheels that exceed the ASA standard angle of attack and the action taken by operators to improve steering performance. Prior to the commencement of operation, the Applicant shall submit for the approval of the Secretary, justification supporting the appropriateness of the location for angle of attack monitoring, the format of the information to be accessible to operators and the format of the public report. The angle of attack monitoring system shall not operate until the Secretary has approved the proposed monitoring location and reporting arrangements.	An Angle of Attack (AoA) monitoring system was installed on the new rail link in May 2020. The monitoring system captures the AoA of each axle passby and compares the measured values with the acceptable value in the applicable Asset Standards Authority minimum operating standard. The AoA values for each axle are available to operators in accordance with the approval condition. A Functional and Performance Specification for the permanent noise monitoring system and angle of attack monitoring system was prepared for approval by the Secretary before the rail link commissioning. A summary of the AoA noise monitoring results of the Year 3 operations is provided in Section 6.1. The monitoring identified 2 trains where the maximum AoA value exceeded the alarm level. None of these events resulted in elevated noise levels at the permanent noise monitoring location. Exceedances of the AoA alarm levels were viewed as one-off instances, occurring irregularly.	Section 6						
G8	The following measures must be implemented during operation: a) The use of automatic rail lubrication equipment in accordance with ASA Standard T HR TR 00111 ST Rail Lubrication and top of rail friction modifiers, where required; and b) Measures to ensure the rail cross sectional profile is maintained in accordance with ETN-01-02 Rail Grinding Manual for Plain Track to ensure the correct wheel / rail contact position and hence to encourage proper rolling stock steering.	Two rail friction modifier systems were installed on the rail link on 22 November 2019 per ASA Standard. These are positioned on the MIMT North Track at Chainage 39.840 km and the MIMT South Track at Chainage 39.580 km. Monthly track inspections and maintenance is undertaken by Qube’s maintenance contractor, Taylor Rail, to ensure alignment with maintenance standards. Rail grinding has been performed so that the rail profile is consistent with maintenance standards.	FCCM 3B						
SSD 7628									
B79	The permitted hours of warehouse and distribution operation as detailed in Table 4. Table 4: Hours of Operation <table><tr><th>Activity</th><th>Day</th><th>Time</th></tr><tr><td>Operation</td><td>Monday to Sunday</td><td>24 hours</td></tr></table>	Activity	Day	Time	Operation	Monday to Sunday	24 hours	MPE operates 24 hours per day, 365 days per year, consistent with the permitted hours of operation.	n/a
Activity	Day	Time							
Operation	Monday to Sunday	24 hours							

Condition ID	Condition	Comments on compliance	Reference for further information																				
B80	B80. Noise generated by operation of the development inclusive of MPE Stage 1 operations must not exceed the noise limits in Table 5.	This condition specifies the operational noise criteria for MPE Stage 1 operations. For each new warehouse and when noise monitoring is undertaken in response to complaints, the measured noise levels are compared with the criteria in this condition.	Section 3																				
	Table 5: Noise Limits dB(A)		Section 7																				
	<table><tr><th>Location (residential receivers)</th><th>Day (LAeq(15min))</th><th>Evening (LAeq(15min))</th><th>Night (LAeq(15min))</th><th>Night (LA1(1min))</th></tr><tr><td>Casula</td><td>35 dB</td><td>35 dB</td><td>35 dB</td><td>52 dB</td></tr><tr><td>Wattle Grove (NCA 2)</td><td>35 dB</td><td>35 dB</td><td>35 dB</td><td>52 dB</td></tr><tr><td>Glenfield (NCA 4)</td><td>35 dB</td><td>35 dB</td><td>35 dB</td><td>52 dB</td></tr></table>		Location (residential receivers)	Day (LAeq(15min))	Evening (LAeq(15min))	Night (LAeq(15min))	Night (LA1(1min))	Casula	35 dB	35 dB	35 dB	52 dB	Wattle Grove (NCA 2)	35 dB	35 dB	35 dB	52 dB	Glenfield (NCA 4)	35 dB	35 dB	35 dB	52 dB	
	Location (residential receivers)		Day (LAeq(15min))	Evening (LAeq(15min))	Night (LAeq(15min))	Night (LA1(1min))																	
	Casula		35 dB	35 dB	35 dB	52 dB																	
	Wattle Grove (NCA 2)		35 dB	35 dB	35 dB	52 dB																	
	Glenfield (NCA 4)		35 dB	35 dB	35 dB	52 dB																	
	Notes:																						
	To determine compliance with the LAeq,15 minute noise limits, noise from the development is to be measured at the most affected point within the residential boundary, or at the most affected point within 30 metres of a dwelling where the dwelling is more than 30 metres from the boundary. Where it can be demonstrated that direct measurement of noise from the project is impractical, the EPA may accept alternative means of determining compliance (see Chapter 11 of the NSW Industrial Noise Policy). The modification factors in Section 4 of the NSW Industrial Noise Policy must also be applied to the measured noise levels where applicable.																						
	To determine compliance with the LA1,1 minute noise limits, noise from the project is to be measured at 1 metre from the dwelling façade. Where it can be demonstrated that direct measurement of noise from the project is impractical, the EPA may accept alternative means of determining compliance (see Chapter 11 of the NSW Industrial Noise Policy).																						
The noise emission limits identified above apply under meteorological conditions of:																							
(i) wind speeds of up to 3 m/s at 10 metres above ground level; or																							
(ii) 'F' atmospheric stability class.																							
B85	The Applicant must carry out noise monitoring of mechanical plant and other noisy equipment for a minimum period of one week where valid data is collected following occupation of each warehouse. The monitoring program must be carried out by a suitably qualified and experienced person(s) and a Monitoring Report for Mechanical Plan must be submitted to the Secretary within two months of occupation or each tenancy to verify predicted mechanical plant and equipment noise levels.	Warehouse noise monitoring is required to be undertaken following the occupation of each warehouse. No additional warehouses commenced operations within the current reporting period.	Section 3																				

Condition ID	Condition	Comments on compliance	Reference for further information
B88	To ensure the operational noise impacts are appropriately managed, the following measures apply: a) use of best practice plant; and b) preparation of a risk assessment to determine if non-tonal reversing alarms can be fitted as a condition of site entry. Alternatively, site design may include traffic flow that does not require or precludes reversing of vehicles.	The following additional best practice plant / measures have been implemented within the current reporting period: 1. The use of electric cranes commenced so that all rail loading and container stacking is performed by the electric cranes, with reach stackers now only required for truck loading. 2. 'Quackers' or broadband reversing alarms were fitted to all reach stackers on site and empty twin pick machines. 3. IMEX truck briefings were undertaken, reminding drivers of noise management obligations and will be ongoing as part of regular reminders. The risk assessment relating to the use of non-tonal reversing alarms is addressed in the Table 2-3 of the ONVMP. [The above measures are consistent with the information provided in QUBE's letter to the Department of Planning and Environment dated circa November 2022]	ONVMP https://moorebankintermodalprecinct.com.au/?cpt_document_library=mpe-s1-onvmp-v12-redacted Section 7
B90	For the duration of operation, the Applicant must: a) continue to implement all reasonable and feasible best practice noise mitigation measures; b) continue to investigate ways to reduce noise generated by the development, including maximum noise levels which may result in sleep disturbance; and c) report on these investigations and the implementation and effectiveness of these measures in the Annual Review to the satisfaction of the Secretary.	The following additional best practice plant / measures have been implemented within the current reporting period: 1. The use of electric cranes commenced so that all rail loading and container stacking is performed by the electric cranes, with reach stackers now only required for truck loading. 2. 'Quackers' or broadband reversing alarms were fitted to all reach stackers on site and empty twin pick machines. 3. IMEX truck briefings were undertaken, reminding drivers of noise management obligations and will be ongoing as part of regular reminders. The permanent rail noise monitoring results (Section 5) for Year 3 operations indicate similar passby noise levels to Year 1 operations and increased L_{Aeq} noise levels consistent with the rail link usage. The AoA monitoring data for train axles is reviewed by operators to identify wagons that may require maintenance to improve steering performance. A noise monitoring program is in progress to review the implemented noise mitigation and management measures and verify site noise emissions against the operational noise emissions requirements (Section 7). [The above measures are consistent with the information provided in QUBE's letter to the Department of Planning and Environment dated circa November 2022]	Sections 3, 4, 5, 6 and 7

Condition ID	Condition	Comments on compliance	Reference for further information
Final Compilation of Mitigation Measures (FCMM) for MPE Stage 1 and Stage 2			
Stage 2 2D	In the event of any noise or vibration related complaint or adverse comment from the community, noise and ground vibration levels (as relevant) would be investigated. Remedial action would be implemented where feasible and reasonable. The procedures for managing complaints would be provided within the Community Information and Awareness Strategy.	A noise monitoring program is in progress to review the implemented noise mitigation and management measures and verify site noise emissions against the operational noise emissions requirements (Section 7).	Section 7
Operational Noise and Vibration Management Plan – Section 4.1.1 Summary of Monitoring Requirements			
Table 4.1 Rail noise monitoring	Continuous rail noise monitoring will be undertaken from the commencement of operations of the IMEX terminal. The monitoring system will capture the following information: - Noise from each train passby - Time and date of each train passby - Imagery or video recording to identify rolling stock - L_AF(max) and Sound Exposure Level (SEL) of individual train passbys, measured in accordance with ISO 3095:2013 - L_Aeq(15hour) and L_Aeq(9hour) noise levels for each 24-hour period, which will be calculated based on the number of train passbys during the day and night periods and the corresponding SEL noise levels, consistent with the procedure in Clause 3.4.1.1 of the Rail Infrastructure Noise Guideline (EPA, 2013). - Other information as required by the Secretary	Refer comments related to SSD 6766 G7	SSD 6766 G7
Wayside Angle of Attack Monitoring	Continuous wayside angle of attack monitoring will be undertaken from the commencement of operations of the IMEX terminal. The monitoring system will capture the following information: - Angle of attack from a wheel on each axle of every train - Time and date of each axle passby - Identification number of each item of rolling stock	Refer comments related to SSD 6766 G7A	SSD 6766 G7A
Brake Squeal Noise	Continuous (unattended monitoring system) from the commencement of operations of the IMEX terminal – to assess potential noise impacts of rail link at western receivers	Refer comments related to SSD 6766 G7. The permanent noise monitoring system is positioned at a location on the rail link where it can capture noise levels associated with curve brake squeal should this occur.	SSD 6766 G7
Operational Noise Monitoring	Noise monitoring to compare actual noise performance of the MLP East Precinct against the noise management levels will be undertaken as follows: - Regular performance monitoring - Within 12 months of the commencement of operation of the IMEX terminal and Warehouse 1 Precinct - Within 12 months of occupation of the first warehouse, 50% occupation of the site and 100% occupation of the site, or as otherwise agreed by the Secretary - For a minimum of 12 months following occupation of the entire site	Sections 3, 4, 5, 6 and 7	Sections 3, 4, 5, 6 and 7

Condition ID	Condition	Comments on compliance	Reference for further information
Operational Noise Monitoring	Attended noise monitoring will be undertaken to determine compliance against the noise management levels upon receipt of a noise complaint	A noise monitoring program is in progress to review the implemented noise mitigation and management measures and verify site noise emissions against the operational noise emissions requirements (Section 7).	Section 7
Noise Assessment of Mechanical Plant	Conducted for the freight village and each warehouse for a period of 1 week after construction and submitted to secretary within 2 weeks of occupation. Compliance against the noise management levels.	Refer comments related to SSD 7628 B85	SSD 7628 B85
Continuous Unattended Noise Monitoring	Continuous noise monitoring will be conducted at the following locations for a period of twelve months following the occupation of the entire site: - CM1: 26 Woodlake Court, Wattle Grove - CM2: 22 Glenelg Court, Wattle Grove North - CM3: 14 Dunmore Crescent, Casula - CM4: 26 Goodenough Street, Glenfield	Refer comments related to SSD 7628 B64 (refer Section 4)	SSD 7628 B64 Section 4

3 Warehouse noise monitoring

Warehouse noise monitoring is required to be undertaken following the occupation of each warehouse. No additional warehouses commenced operations within the reporting period.

4 Continuous noise monitoring in residential areas

Continuous noise monitoring at sensitive receivers is required to be undertaken at sensitive receivers in accordance with the approval conditions for MPE Stage 2 (SSD 7628 Condition B64). Whilst this condition relates to construction noise, the noise monitoring results can also be utilised to measure operational noise and to investigate noise complaints (if required).

Details of the continuous noise monitoring and measurement locations (CM1 to CM4) are provided in Section 4.1.2 and Figure 3-1 of the CNVMP. The measurement systems comprise four Envirosuite permanent noise monitors.

The primary purpose of the permanent noise monitoring systems is to measure construction-related noise in accordance with the requirements of SSD 7628 Condition B64. This noise monitoring is ongoing.

5 Continuous rail link noise monitoring

The commencement of Intermodal Terminal operations occurred in May 2020. The new rail link was commissioned earlier in November 2019. In conjunction with the rail link commissioning, a temporary rail noise monitoring system (RNMS) was established to quantify the passby noise levels in accordance with the requirements of SSD6766 Condition G7.

The temporary RNMS was positioned at a location near one of the small radius curves and where freight trains are likely to be braking. The microphone of the RNMS monitoring system was positioned on the western side of rail link at a distance of 10.5 m from the near track centreline (Up track) and 15.5 m from the far track centreline (Down track).

The temporary RNMS was operational between 1 November 2019 and 8 July 2020. During this period, procurement of a permanent noise monitoring system occurred, compliant with the requirements of the *Functional and Performance Specification for Permanent Noise Monitor and Proposed Noise and AoA Monitoring Locations*. This functional specification provided justification supporting the appropriateness of the proposed monitoring location and was approved by the Secretary.

The permanent noise monitoring system was commissioned on 9 July 2020 at the same location as the temporary RNMS. The permanent system incorporates two microphones, one adjacent to each track, at a distance of 7.5 m from the track centreline. Noise measurement results of all passbys are provided [here](#)¹.

Below is a summary of the noise monitoring results for Year 3 operations.

5.1 Year 3 rail operations noise monitoring report

This report covers rail movements between 10 May 2022 and 9 May 2023. A summary of the key statistics are provided below:

- Number of days in monitoring period - 365 days.
- Number of valid train passby events – 864 (day), 301 (night), 1165 (day + night)
- Number of days that included one or more train events – 316, representing 87% of days (6.1 days per week)
- Number of nights that included one or more train events – 207, representing 57% of nights (4.0 nights per week)

¹ Available <https://moorebanknoisemonitor-emsbk.trackiq.net/NoiseMonitor/>


For each train passby, the noise monitoring system recorded the L_{AFmax} and SEL^2 noise levels at a measurement distance of 7.5 m from the track centreline. The SEL noise levels are utilised to calculate the $L_{Aeq(15hour)}$ daytime and $L_{Aeq(9hour)}$ noise levels each day.

A summary of the measured $L_{Aeq(15hour)}$ daytime noise levels, normalised to a measurement distance of 30 m is provided in Figure 1. The corresponding noise levels for the night-time period are provided in Figure 2.

It is noted that the nearest residential receiver (Glenfield Farm) is approximately 400 m from the rail link at the closest point and approximately 850 m from the noise monitoring system. The noise levels at Glenfield Farm are estimated to be approximately 14 dB(A) or more below the values in Figure 1 and Figure 2.


Based on the results in Figure 1 and Figure 2, the measured $L_{Aeq(15hour)}$ and $L_{Aeq(9hour)}$ noise levels appear to be approximately 5 dB(A) higher than the Year 1 noise monitoring results (see Reference 3). This increase is related to the increased usage of the rail link between Year 1 and Year 3 (i.e. additional trains), rather than a result of increased noise levels from individual train passbys.

Figure 1 Measured $L_{Aeq(15hour)}$ daytime noise levels at 30 m from track centreline



² SEL represents the single-event Sound Exposure Level of the train passby. This represents the total noise energy of the train passby event, normalised to a measurement interval of one second. The SEL is expressed as a dB(A) noise level.

³ Moorebank Intermodal Terminal Annual Noise Review - April 2021, Renzo Tonin & Associates Report TL116-05F11 Annual Review April 2021 (r2) dated 21 June 2021

Figure 2 Measured $L_{Aeq(9hour)}$ night-time noise levels at 30 m from track centreline

A summary of the measured L_{AFmax} daytime noise levels at a measurement distance of 7.5 m is provided in Figure 3. The corresponding noise levels for the night-time period are provided in Figure 4.



Figure 3 Measured L_{AFmax} daytime noise levels at 7.5 m from track centreline

Figure 4 Measured L_{AFmax} night-time noise levels at 7.5 m from track centreline

Based on the results in Figure 3 and Figure 4, there does not appear to be any obvious trend in the measured L_{AFmax} noise levels during the monitoring period. The maximum noise levels are consistent with the Year 1 noise monitoring results (see Reference 3).

6 Rail link angle of attack (AoA) monitoring

The performance of wagon bogies and their ability to negotiate small radius curves without generating curve squeal, is assessed in terms of the angle of attack (AoA) of the wheelset. Acceptable AoA values are defined in Section 2.7.1 of Asset Standards Authority Standard T HR RS 00400 ST⁴ and are a function of the curve radius and wheel base.

An AoA measurement system was installed on the rail link and partially commissioned on 13 May 2020. The system was fully commissioned on 9 July 2020 at the same time as the permanent noise monitoring system. The AoA system is installed on the eastern track.

Justification supporting the appropriateness of the proposed monitoring location is provided in the *Functional and Performance Specification for Permanent Noise Monitor and Proposed Noise and AoA Monitoring Locations*⁵, and was approved by the Secretary.

The AoA monitoring system was off-line for the period between 28 April 2022 and 1 December 2022. Additional details are provided in the letter from QUBE to the Department of Planning and Environment dated 9/12/2022.

AoA measurement data for Year 3 operations is available in the following six monthly report:

- Moorebank Intermodal Terminal - Six Monthly Review of AoA – May 2023
(rail movements between 1 December 2022 and 30 April 2023)

In accordance with the requirements of the SSD 6766 Condition G7A, the AoA of a wheel of each axle of each train is captured by the measurement system. This data is accessible by train operators on a website maintained by QUBE.

Below is a summary of the noise monitoring results for Year 3 operations.

6.1 Year 3 rail operations AoA monitoring

A summary of the key statistics are provided below:

- 1 December 2022 and 30 April 2023
 - Number of valid train passby events – 190
 - Number of train passby events where the measure AoA values on one or more axles were above the acceptable level defined in Section 2.7.1 of Asset Standards Authority Standard T HR RS 00400 ST – 2, representing 1% of passbys.


⁴ Transport for NSW Asset Standards Authority T HR RS 00400 ST *RSU 400 Series – Minimum Operating Standards for Rolling Stock – Freight Vehicle Specific Interface Requirements* Version 2.0 dated 24 August 2017

⁵ Renzo Tonin & Associates Report TJ741-04F04 AoA and Functional Spec for Permanent Noise Monitor (r8)

A summary of the maximum AoA value measured for each train is provided in Figure 5. The results show that the maximum AoA value is typically less than 10 mrad. 2 train passbys had maximum AoA values greater than the established alarm level of approximately 19 mrad.

None of these AoA alarm events resulted in elevated noise levels at the permanent noise monitoring location (refer Section 5.1). Exceedances of the AoA alarm levels were viewed as one-off instances, occurring irregularly.

Figure 5 Maximum AoA value for each train - 1 December 2022 and 30 April 2023



7 Noise monitoring in response to complaints

In the current reporting period, a number of complaints relating to operational noise levels were reported by residents in Wattle Grove. The complaints related to container movement noise, on-site truck noise and general night-time / early morning noise (related to hours of operation).

The number of operational noise-related complaints each month is summarised in the below table. The number noise complaints were highest in July and August 2022. No noise complaints were received in the last seven months of the current reporting period.

Period	Number of operational noise-related complaints
April 2022	0
May 2022	0
June 2022	2
July 2022	5
August 2022	10
September 2022	1
October 2022	0
November 2022	0
December 2022	0
January 2023	0
February 2023	0
March 2023	0
April 2023	0

In response to the operational noise complaints received in June / July 2022, QUBE promptly responded by reviewing the noise monitoring results from the continuous noise monitors (refer Section 4), and subsequently engaged Renzo Tonin & Associates to carry out a detailed noise investigation.

An initial detailed noise investigation was conducted at four representative receivers in Wattle Grove between Friday 5 August 2022 and Saturday 6 August 2022. The results of this investigation are set out in the Operational Noise Complaint Investigation report dated 15 August 2022 (the August Investigation Report), which was provided to the Department of Planning and Environment on 28 September 2022.

The August Investigation Report did not identify any non-compliances with the operational noise criteria in the Consent. However, given the number of complaints received, QUBE committed to undertaking further noise monitoring in the community to review the ongoing implementation of noise mitigation and management measures.

Renzo Tonin and Associates were subsequently engaged to undertake a Noise Measurement Program to review the following noise mitigation measures that were implemented by the development:

- a) Commencement of container stacking to east of the IMEX terminal, forming a defacto noise barrier as the container stacks will provide a natural mitigation barrier for noise to the east

- b) The commencement of electric cranes, with all rail loading and container stacking performed by the electric cranes with reach stackers only required for truck loading
- c) 'Quackers' or broadband reversing alarms were fitted to all reach stackers onsite and empty twin pick machines
- d) IMEX truck briefings were undertaken reminding drivers of noise management obligations and will be ongoing as part of regular reminders.

This noise monitoring program remains ongoing and includes:

- Observations of on-site activities to review implemented noise mitigation and management measures and aid the effectiveness of the operational noise measurement program.
- At-receiver noise monitoring to verify site noise emissions against the operational noise emissions requirements. These measurements will be performed on three separate occasions during periods that are representative of typical operations.
- Reporting of the outcomes of the above investigation.
- Unattended noise monitoring to review ongoing operational noise performance.

Details of the above program were provided to the Department of Planning and Environment in November 2022. The outcomes of the noise monitoring program will be made available to the Department of Planning and Environment at the conclusion of the program.

8 Other noise-related tasks

8.1 IMEX operations

Mitigation and management measures are being investigated as part of proposals to increase the IMEX throughput, which include consideration of cumulative impacts across the Moorebank Intermodal Precinct. This includes both mitigation and management measures for noise emissions and maximum noise levels which may result in sleep disturbance.

This work is ongoing.

8.2 Warehouse operations and Moorebank Noise Management Precinct

Planning work is underway for the implementation of the Moorebank Noise Management Precinct. This includes allocation of noise quotas to warehouse operations, to manage cumulative noise emissions as part of the Moorebank Noise Management Precinct.

9 Conclusion

This **Annual Noise Review** report **for Year 3 Operations** has been prepared to address the requirements of Approval Condition B90 of SSD 7628.

The following operational noise monitoring has been performed in accordance the Approval Conditions in SSD 6766 and 7628:

- Continuous rail noise and angle of attack (AoA) monitoring on the rail link to monitoring rail traffic noise and to assist in identifying potential high noise events (e.g. excessive locomotive noise, brake squeal or curve squeal).
- Noise monitoring has been undertaken in response to complaints received from residents in Wattle Grove between June and September 2022. In response to these complaints, additional noise mitigation and management measures were implemented and a noise management program is in progress to review their effectiveness.

APPENDIX A Glossary of terminology

The following is a brief description of the technical terms used to describe noise to assist in understanding the technical issues presented.

Absorption Coefficient α	The absorption coefficient of a material, usually measured for each octave or third-octave band and ranging between zero and one. For example, a value of 0.85 for an octave band means that 85% of the sound energy within that octave band is absorbed on coming into contact with the material. Conversely, a low value below about 0.1 means the material is acoustically reflective.
Adverse weather	Weather effects that enhance noise (particularly wind and temperature inversions) occurring at a site for a significant period of time. In the NSW INP this occurs when wind occurs for more than 30% of the time in any assessment period in any season and/or temperature inversions occurring more than 30% of nights in winter.
Air-borne noise	Noise which is fundamentally transmitted by way of the air and can be attenuated by the use of barriers and walls placed physically between the noise source and receiver.
Ambient noise	The all-encompassing noise associated within a given environment at a given time, usually composed of sound from all sources near and far.
AoA	Angle of Attack - As the wheels on a bogie negotiate a tight curve, the leading wheelset typically presents an Angle-of-Attack (AoA) to the rail. The AoA of a leading wheelset with good steering performance can be calculated from $AoA = \text{wheelbase (m)} / \text{curve radius (m)}$. AoA is normally measured in milliradian (mrad).
Amenity	A desirable or useful feature or facility of a building or place.
AS	Australian Standard
ASA	Asset Standards Authority
Assessment period	The time period in which an assessment is made. e.g. Day 7am-10pm & Night 10pm-7am.
Assessment Point	A location at which a noise or vibration measurement is taken or estimated.
Attenuation	The reduction in the level of sound or vibration.
Audible Range	The limits of frequency which are audible or heard as sound. The normal hearing in young adults detects ranges from 20 Hz to 20 kHz, although some people can detect sound with frequencies outside these limits.
A-weighting	A filter applied to the sound recording made by a microphone to approximate the response of the human ear.
Background noise	Background noise is the term used to describe the underlying level of noise present in the ambient noise, measured in the absence of the noise under investigation. It is described as the average of the minimum noise levels measured on a sound level meter and is measured statistically as the A-weighted noise level exceeded for ninety percent of a sample period. This is represented as the LA90 noise level if measured as an overall level or an L90 noise level when measured in octave or third-octave bands.
Barrier (Noise)	A natural or constructed physical barrier which impedes the propagation of sound and includes fences, walls, earth mounds or berms and buildings.
Berm	Earth or overburden mound.
Buffer	An area of land between a source and a noise-sensitive receiver and may be an open space or a noise-tolerant land use.
Bund	A bund is an embankment or wall of brick, stone, concrete or other impervious material, which may form part or all of the perimeter of a compound.
BS	British Standard

CoRTN	United Kingdom Department of Environment entitled “Calculation of Road Traffic Noise (1988)”		
Decibel [dB]	The units that sound is measured in. The following are examples of the decibel readings of common sounds in our environment:		
	threshold of hearing	0 dB	The faintest sound we can hear, defined as 20 micro Pascal
		10 dB	Human breathing
	almost silent	20 dB	
		30 dB	Quiet bedroom or in a quiet national park location
	generally quiet	40 dB	Library
		50 dB	Typical office space or ambience in the city at night
	moderately loud	60 dB	CBD mall at lunch time
		70 dB	The sound of a car passing on the street
	loud	80 dB	Loud music played at home
		90 dB	The sound of a truck passing on the street
	very loud	100 dB	Indoor rock band concert
		110 dB	Operating a chainsaw or jackhammer
	extremely loud	120 dB	Jet plane take-off at 100m away
threshold of pain	130 dB		
	140 dB	Military jet take-off at 25m away	
dB(A)	A-weighted decibel. The A- weighting noise filter simulates the response of the human ear at relatively low levels, where the ear is not as effective in hearing low frequency sounds as it is in hearing high frequency sounds. That is, low frequency sounds of the same dB level are not heard as loud as high frequency sounds. The sound level meter replicates the human response of the ear by using an electronic filter which is called the “A” filter. A sound level measured with this filter is denoted as dB(A). Practically all noise is measured using the A filter.		
dB(C)	C-weighted decibels. The C-weighting noise filter simulates the response of the human ear at relatively high levels, where the human ear is nearly equally effective at hearing from mid-low frequency (63Hz) to mid-high frequency (4kHz), but is less effective outside these frequencies. The dB(C) level is not widely used but has some applications.		
Diffraction	The distortion of sound waves caused when passing tangentially around solid objects.		
DIN	German Standard		
ECRTN	Environmental Criteria for Road Traffic Noise, NSW, 1999		
ENMM	Environmental Noise Management Manual, Roads and Maritime Services (Transport for NSW)		
EPA	Environment Protection Authority		
Field Test	A test of the sound insulation performance in-situ. See also 'Laboratory Test' The sound insulation performance between building spaces can be measured by conducting a field test, for example, early during the construction stage or on completion. A field test is conducted in a non-ideal acoustic environment. It is generally not possible to measure the performance of an individual building element accurately as the results can be affected by numerous field conditions.		
Fluctuating Noise	Noise that varies continuously to an appreciable extent over the period of observation.		
Free-field	An environment in which there are no acoustic reflective surfaces. Free field noise measurements are carried out outdoors at least 3.5m from any acoustic reflecting structures other than the ground.		
Frequency	Frequency is synonymous to pitch. Sounds have a pitch which is peculiar to the nature of the sound generator. For example, the sound of a tiny bell has a high pitch and the sound of a bass drum has a low pitch. Frequency or pitch can be measured on a scale in units of Hertz or Hz.		

Ground-borne noise	Vibration propagated through the ground and then radiated as noise by vibrating building elements such as wall and floor surfaces. This noise is more noticeable in rooms that are well insulated from other airborne noise. An example would be vibration transmitted from an underground rail line radiating as sound in a bedroom of a building located above.
Habitable Area	Includes a bedroom, living room, lounge room, music room, television room, kitchen, dining room, sewing room, study, playroom, family room, home theatre and sunroom. Excludes a bathroom, laundry, water closet, pantry, walk-in wardrobe, corridor, hallway, lobby, photographic darkroom, clothes drying room, and other spaces of a specialised nature occupied neither frequently nor for extended periods.
Heavy Vehicle	A truck, transporter or other vehicle with a gross weight above a specified level (for example: over 8 tonnes).
IGANRIP	Interim Guideline for the Assessment of Noise from Rail Infrastructure Projects, NSW DEC 2007
Impulsive noise	Having a high peak of short duration or a sequence of such peaks. A sequence of impulses in rapid succession is termed repetitive impulsive noise.
INP	NSW Industrial Noise Policy, EPA 1999
Intermittent noise	The level suddenly drops to that of the background noise several times during the period of observation. The time during which the noise remains at levels different from that of the ambient is one second or more.
Intrusive noise	Refers to noise that intrudes above the background level by more than 5 dB(A).
ISEPP	State Environmental Planning Policy (Infrastructure), NSW, 2007
ISEPP Guideline	Development Near Rail Corridors and Busy Roads - Interim Guideline, NSW Department of Planning, December 2008
L1	The sound pressure level that is exceeded for 1% of the time for which the given sound is measured.
L10	The sound pressure level that is exceeded for 10% of the time for which the given sound is measured.
L10(1hr)	The L10 level measured over a 1 hour period.
L10(18hr)	The arithmetic average of the L10(1hr) levels for the 18 hour period between 6am and 12 midnight on a normal working day.
L90	The level of noise exceeded for 90% of the time. The bottom 10% of the sample is the L90 noise level expressed in units of dB(A).
LAeq or Leq	The "equivalent noise level" is the summation of noise events and integrated over a selected period of time, which would produce the same energy as a fluctuating sound level. When A-weighted, this is written as the LAeq.
LAeq(1hr)	The LAeq noise level for a one-hour period. In the context of the NSW EPA's Road Noise Policy it represents the highest tenth percentile hourly A-weighted Leq during the period 7am to 10pm, or 10pm to 7am (whichever is relevant).
LAeq(8hr)	The LAeq noise level for the period 10pm to 6am.
LAeq(9hr)	The LAeq noise level for the period 10pm to 7am.
LAeq(15hr)	The LAeq noise level for the period 7am to 10pm.
LAeq (24hr)	The LAeq noise level during a 24 hour period, usually from midnight to midnight.
Lmax	The maximum sound pressure level measured over a given period. When A-weighted, this is usually written as the L _{Amax} .
Lmin	The minimum sound pressure level measured over a given period. When A-weighted, this is usually written as the L _{Amin} .
Loudness	A rise of 10 dB in sound level corresponds approximately to a doubling of subjective loudness. That is, a sound of 85 dB is twice as loud as a sound of 75 dB which is twice as loud as a sound of 65 dB and so on. That is, the sound of 85 dB is four times or 400% the loudness of a sound of 65 dB.

Microphone	An electro-acoustic transducer which receives an acoustic signal and delivers a corresponding electric signal.
MPE	Moorebank Precinct East
NCA	Noise Catchment Area. An area of study within which the noise environment is substantially constant.
NCG	Noise Criteria Guideline, Roads and Maritime Services (Transport for NSW)
NMG	Noise Mitigation Guideline, Roads and Maritime Services (Transport for NSW)
Noise	Unwanted sound
Pre-construction	Work in respect of the proposed project that includes design, survey, acquisitions, fencing, investigative drilling or excavation, building/road dilapidation surveys, minor clearing (except where threatened species, populations or ecological communities would be affected), establishing ancillary facilities such as site compounds, or other relevant activities determined to have minimal environmental impact (e.g. minor access roads).
Reflection	Sound wave reflected from a solid object obscuring its path.
RING	Rail Infrastructure Noise Guideline, NSW, May 2013
RMS	Root Mean Square value representing the average value of a signal.
Rw	Weighted Sound Reduction Index A measure of the sound insulation performance of a building element. It is measured in very controlled conditions in a laboratory. The term supersedes the value STC which was used in older versions of the Building Code of Australia. Rw is measured and calculated using the procedure in ISO 717-1. The related field measurement is the DnT,w. The higher the value the better the acoustic performance of the building element.
R'w	Weighted Apparent Sound Reduction Index. As for Rw but measured in-situ and therefore subject to the inherent accuracies involved in such a measurement. The higher the value the better the acoustic performance of the building element.
RNP	Road Noise Policy, NSW, March 2011
Sabine	A measure of the total acoustic absorption provided by a material. It is the product of the Absorption Coefficient (alpha) and the surface area of the material (m ²). For example, a material with alpha = 0.65 and a surface area of 8.2m ² would have 0.65 x 8.2 = 5.33 Sabine. Sabine is usually calculated for each individual octave band (or third-octave).
SEL	Sound Exposure Level (SEL) is the constant sound level which, if maintained for a period of 1 second would have the same acoustic energy as the measured noise event. SEL noise measurements are useful as they can be converted to obtain Leq sound levels over any period of time and can be used for predicting noise at various locations.
Sound	A fluctuation of air pressure which is propagated as a wave through air.
Sound absorption	The ability of a material to absorb sound energy by conversion to thermal energy.
Sound Insulation	Sound insulation refers to the ability of a construction or building element to limit noise transmission through the building element. The sound insulation of a material can be described by the Rw and the sound insulation between two rooms can be described by the DnT,w.
Sound level meter	An instrument consisting of a microphone, amplifier and indicating device, having a declared performance and designed to measure sound pressure levels.
Sound power level	Ten times the logarithm to the base 10 of the ratio of the sound power of the source to the reference sound power of 1 pico watt.
Sound pressure level	The level of noise, usually expressed in decibels, as measured by a standard sound level meter with a microphone referenced to 20 micro Pascal.
Spoil	Soil or materials arising from excavation activities.

SSFL	Southern Sydney Freight Line
STC	Sound Transmission Class A measure of the sound insulation performance of a building element. It is measured in controlled conditions in a laboratory. The term has been superseded by R_w.
Structure-borne Noise	Audible noise generated by vibration induced in the ground and/or a structure. Vibration can be generated by impact or by solid contact with a vibrating machine. Structure-borne noise cannot be attenuated by barriers or walls but requires the isolation of the vibration source itself. This can be achieved using a resilient element placed between the vibration source and its support such as rubber, neoprene or springs or by physical separation (using an air gap for example). Examples of structure-borne noise include the noise of trains in underground tunnels heard to a listener above the ground, the sound of footsteps on the floor above a listener and the sound of a lift car passing in a shaft. See also 'Impact Noise'.
Tonal Noise	Sound containing a prominent frequency and characterised by a definite pitch.
Transmission Loss	The sound level difference between one room or area and another, usually of sound transmitted through an intervening partition or wall. Also the vibration level difference between one point and another. For example, if the sound level on one side of a wall is 100dB and 65dB on the other side, it is said that the transmission loss of the wall is 35dB. If the transmission loss is normalised or standardised, it then becomes the R_w or $R'w$ or $D_{nT,w}$.
Wheelbase	The wheelbase is the distance between the centres of the front and rear wheels on a 2-axle bogie.

APPENDIX B Detailed noise assessment reports

B.1 Angle of Attack Monitoring Report - 1 December 2022 and 30 April 2023

Renzo Tonin Report TL116-05F20 AoA Report May 2023 (r2)

MOOREBANK INTERMODAL TERMINAL

Six Monthly Review of AoA - May 2023

5 July 2023

Tactical Group

TL116-05F20 AoA Report May 2023 (r2).docx

Document details

Detail	Reference
Doc reference:	TL116-05F20 AoA Report May 2023 (r2).docx
Prepared for:	Tactical Group
Address:	Level 15, 124 Walker Street North Sydney, NSW, 2060
Attention:	

Document control

Date	Revision history	Non-issued revision	Issued revision	Prepared	Instructed	Reviewed / Authorised
25.05.2023	First Issue	0	1			
25.07.2023	Final	-	2			
File Path: R:\AssocSydProjects\TL101-TL150\TL116 - cw Moorebank IMT Temporary Noise Monitoring\Task 5 - cw Operation Compliance Monitoring\1 Docs\Report 20 2023-05 AoA\TL116-05F20 AoA Report May 2023 (r2).docx						

Important Disclaimers:

The work presented in this document was carried out in accordance with the Renzo Tonin & Associates Quality Assurance System, which is based on Australian/New Zealand Standard AS/NZS ISO 9001.

This document is issued subject to review and authorisation by the suitably qualified and experienced person named in the last column above. If no name appears, this document shall be considered as preliminary or draft only and no reliance shall be placed upon it other than for information to be verified later.

This document is prepared for the particular requirements of our Client referred to above in the 'Document details' which are based on a specific brief with limitations as agreed to with the Client. It is not intended for and should not be relied upon by a third party and no responsibility is undertaken to any third party without prior consent provided by Renzo Tonin & Associates. The information herein should not be reproduced, presented or reviewed except in full. Prior to passing on to a third party, the Client is to fully inform the third party of the specific brief and limitations associated with the commission.

In preparing this report, we have relied upon, and presumed accurate, any information (or confirmation of the absence thereof) provided by the Client and/or from other sources. Except as otherwise stated in the report, we have not attempted to verify the accuracy or completeness of any such information. If the information is subsequently determined to be false, inaccurate or incomplete then it is possible that our observations and conclusions as expressed in this report may change.

We have derived data in this report from information sourced from the Client (if any) and/or available in the public domain at the time or times outlined in this report. The passage of time, manifestation of latent conditions or impacts of future events may require further examination and re-evaluation of the data, findings, observations and conclusions expressed in this report.

We have prepared this report in accordance with the usual care and thoroughness of the consulting profession, for the sole purpose described above and by reference to applicable standards, guidelines, procedures and practices at the date of issue of this report. For the reasons outlined above, however, no other warranty or guarantee, whether expressed or implied, is made as to the data, observations and findings expressed in this report, to the extent permitted by law.

The information contained herein is for the purpose of acoustics only. No claims are made and no liability is accepted in respect of design and construction issues falling outside of the specialist field of acoustics engineering including and not limited to structural integrity, fire rating, architectural buildability and fit-for-purpose, waterproofing and the like. Supplementary professional advice should be sought in respect of these issues.

External cladding disclaimer: No claims are made and no liability is accepted in respect of any external wall and/or roof systems (eg facade / cladding materials, insulation etc) that are: (a) not compliant with or do not conform to any relevant non-acoustic legislation, regulation, standard, instructions or Building Codes; or (b) installed, applied, specified or utilised in such a manner that is not compliant with or does not conform to any relevant non-acoustic legislation, regulation, standard, instructions or Building Codes.

Contents

1	Introduction	1
1.1	Project overview	1
2	Compliance Matrix	2
3	Rail link angle of attack (AoA) monitoring	5
3.1	AoA monitoring results for current six-month period	5
4	Conclusion	7
APPENDIX A	Glossary of terminology	8

List of tables

Table 1	Compliance matrix	3
---------	-------------------	---

List of figures

Figure 1	Maximum AoA value for each train passby	6
----------	---	---

1 Introduction

1.1 Project overview

The Sydney Intermodal Terminal Alliance (SIMTA) received approval for the construction and operation of Stages 1 and 2 of the Moorebank Precinct East (MPE) Project (SSD 6766 and SSD 7628 respectively), which together comprise the two stages of development under the MPE Concept Approval (MP10_0193).

This report has been prepared to address the requirements of Approval Condition G7A of SSD 6766, which requires the submission of a six-monthly report to the Secretary, which identifies the number of wagons with wheels that exceed the ASA standard angle of attack and the action taken by operators to improve steering performance.

Appendix A contains a glossary of acoustic terms used in this report.

2 Compliance Matrix

Table 1 provides a summary of the Approval Conditions which relate to this report.

Table 1 Compliance matrix

Condition ID	Condition	Comments on compliance	Reference for further information
SSD 6766			
G7	The Applicant shall install and maintain a rail noise monitoring system on the rail link at the commencement of operation to continuously monitor the noise from rail operations on the rail link. The system shall capture the noise from each individual train passby noise generation event, and include information to identify: a) Time and date of freight train passbys; b) Imagery or video to enable identification of the rolling stock during day and night; c) $L_{Aeq(15hour)}$ and $L_{Aeq(9hour)}$ from rail operations; and d) $L_{AF(max)}$ and SEL of individual train passbys, measured in accordance with ISO3095; or e) Other alternative information as agreed with, or required by, the Secretary. The results from the noise monitoring system, shall be publicly accessible from a website maintained by the Applicant. The noise results from each train shall be available on the website within 24 hours of it passing the monitor, unless unforeseen circumstances (i.e a system malfunction) have occurred. The $L_{Aeq(15hour)}$ and $L_{Aeq(9hr)}$ results from each day shall be available on the website within 24 hours of the period ending. Prior to the commencement of operation, the Applicant shall submit for the approval of the Secretary, justification supporting the appropriateness of the location for rail noise monitoring, including details of any alternative options considered and reasons for these being dismissed. The rail noise monitoring system shall not operate until the Secretary has approved the proposed monitoring location. The Applicant shall provide an annual report to the Secretary with the results of monitoring for a period of 5 years, or as otherwise agreed with the Secretary, from the commencement of operation of the IMEX terminal. The Secretary shall consider the need for further reporting following a review of the results for year 5.	This condition is not directly related to this report. It is referenced herein on the basis that noise levels from the rail noise monitoring system provides information that may correlate with the Angle of Attack measurement results.	https://moorebankintermodalprecinct.com.au/wp-content/uploads/2023/04/TJ741-04F04-AoA-and-Functional-Spec-for-Permanent-Noise-Monitor-r9_redacted.pdf https://moorebanknoisemonitor-emsbk.trackiq.net/NoiseMonitor/

Condition ID	Condition	Comments on compliance	Reference for further information
G7A	The applicant shall install and maintain a wayside angle of attack monitoring system on the rail link at the commencement of operation to continuously monitor the angle of attack to the rail of rolling stock wheels. The system shall capture the angle of attack from a wheel on each axle of every train, and include information to identify: - Time and date of each axle passby; and - The identification number of each item of rolling stock. The results from the angle of attack monitoring system shall be: - accessible by train operators from a website maintained by the Applicant. Angle of attack results from each train shall be available on the website within 24 hours of it passing the monitor, unless unforeseen circumstances have occurred. - included in a six-monthly report to the Secretary. The report should at least identify the number of wagons with wheels that exceed the ASA standard angle of attack and the action taken by operators to improve steering performance. Prior to the commencement of operation, the Applicant shall submit for the approval of the Secretary, justification supporting the appropriateness of the location for angle of attack monitoring, the format of the information to be accessible to operators and the format of the public report. The angle of attack monitoring system shall not operate until the Secretary has approved the proposed monitoring location and reporting arrangements.	An Angle of Attack (AoA) monitoring system was installed on the new rail link in May 2020. The monitoring system captures the AoA of each axle passby and compares the measured values with the acceptable value in the applicable Asset Standards Authority minimum operating standard. The AoA values for each axle are available to operators in accordance with the approval condition. A Functional and Performance Specification for the permanent noise monitoring system and angle of attack monitoring system was prepared for approval by the Secretary before the rail link commissioning. A summary of the AoA noise monitoring results for the current six month period is provided in Section 3.1. The monitoring identified 2 trains where the maximum AoA value exceeded the alarm level. None of these events resulted in elevated noise levels at the permanent noise monitoring location. These were viewed as one-off instances, occurring irregularly.	Section 3

3 Rail link angle of attack (AoA) monitoring

The performance of wagon bogies and their ability to negotiate small radius curves without generating curve squeal, is assessed in terms of the angle of attack (AoA) of the wheelset. Acceptable AoA values are defined in Section 2.7.1 of Asset Standards Authority Standard T HR RS 00400 ST¹ and are a function of the curve radius and wheel base.

An AoA measurement system was installed on the rail link and partially commissioned on 13 May 2020. The system was fully commissioned on 9 July 2020 at the same time as the permanent noise monitoring system. The AoA system is installed on the eastern track.

Justification supporting the appropriateness of the proposed monitoring location is provided in the *Functional and Performance Specification for Permanent Noise Monitor and Proposed Noise and AoA Monitoring Locations*², and was approved by the Secretary.

This report provides a summary of the AoA measurement data for the period between 1 December 2022 and 30 April 2023. In accordance with the requirements of the SSD 6766 Condition G7A, the AoA of a wheel of each axle of each train is captured by the measurement system. This data is accessible by train operators on a website maintained by QUBE.

Below is a summary of the monitoring results.

3.1 AoA monitoring results for current six-month period

This report covers rail movements between 1 December 2022 and 30 April 2023. A summary of the key statistics is provided below:

- Number of valid train passby events – **190**
- Number of train passby events where the measure AoA values on one or more axles were above the acceptable level defined in Section 2.7.1 of Asset Standards Authority Standard T HR RS 00400 ST – **2** (representing 1% of passbys).


A summary of the maximum AoA value measured for each train is provided in Figure 1. The results show that the maximum AoA value is typically less than 10 mrad. Two train passbys had maximum AoA values greater than the established alarm level of approximately 19 mrad. These were viewed as one-off instances, occurring irregularly, and further rectification actions by the train operator as a result are not deemed required.

¹ Transport for NSW Asset Standards Authority T HR RS 00400 ST *RSU 400 Series – Minimum Operating Standards for Rolling Stock – Freight Vehicle Specific Interface Requirements* Version 2.0 dated 24 August 2017

² Renzo Tonin & Associates Report TJ741-04F04 AoA and Functional Spec for Permanent Noise Monitor (r8) – available https://moorebankintermodalprecinct.com.au/wp-content/uploads/2023/04/TJ741-04F04-AoA-and-Functional-Spec-for-Permanent-Noise-Monitor-r9_redacted.pdf

None of these AoA alarm events resulted in elevated noise levels at the permanent noise monitoring location [i.e. where the calculated $L_{Aeq(9\text{hour})}$ noise levels at 30 m were above 60 dB(A)].

Figure 1 Maximum AoA value for each train passby



4 Conclusion

This report has been prepared to address the requirements of Approval Condition G7A of SSD 6766, which requires the submission of a six-monthly report to the Secretary, which identifies the number of train passbys and wagons with wheels that exceed the ASA standard angle of attack and the action taken by operators to improve steering performance.

For rail movements between 1 December 2022 and 30 April 2023, two train passbys had maximum AoA values greater than the established alarm level of approximately 19 mrad. These were viewed as one-off instances, occurring irregularly and further rectification actions by the train operator as a result are not deemed required. None of these events resulted in elevated noise levels at the permanent noise monitoring location [i.e. where the calculated $L_{Aeq(9hour)}$ noise levels at 30 m were above 60 dB(A)].

APPENDIX A Glossary of terminology

The following is a brief description of the technical terms used to describe noise to assist in understanding the technical issues presented.

Absorption Coefficient α	The absorption coefficient of a material, usually measured for each octave or third-octave band and ranging between zero and one. For example, a value of 0.85 for an octave band means that 85% of the sound energy within that octave band is absorbed on coming into contact with the material. Conversely, a low value below about 0.1 means the material is acoustically reflective.
Adverse weather	Weather effects that enhance noise (particularly wind and temperature inversions) occurring at a site for a significant period of time. In the NSW INP this occurs when wind occurs for more than 30% of the time in any assessment period in any season and/or temperature inversions occurring more than 30% of nights in winter.
Air-borne noise	Noise which is fundamentally transmitted by way of the air and can be attenuated by the use of barriers and walls placed physically between the noise source and receiver.
Ambient noise	The all-encompassing noise associated within a given environment at a given time, usually composed of sound from all sources near and far.
AoA	Angle of Attack - As the wheels on a bogie negotiate a tight curve, the leading wheelset typically presents an Angle-of-Attack (AoA) to the rail. The AoA of a leading wheelset with good steering performance can be calculated from $AoA = \text{wheelbase (m)} / \text{curve radius (m)}$. AoA is normally measured in milliradian (mrad).
Amenity	A desirable or useful feature or facility of a building or place.
AS	Australian Standard
ASA	Asset Standards Authority
Assessment period	The time period in which an assessment is made. e.g. Day 7am-10pm & Night 10pm-7am.
Assessment Point	A location at which a noise or vibration measurement is taken or estimated.
Attenuation	The reduction in the level of sound or vibration.
Audible Range	The limits of frequency which are audible or heard as sound. The normal hearing in young adults detects ranges from 20 Hz to 20 kHz, although some people can detect sound with frequencies outside these limits.
A-weighting	A filter applied to the sound recording made by a microphone to approximate the response of the human ear.
Background noise	Background noise is the term used to describe the underlying level of noise present in the ambient noise, measured in the absence of the noise under investigation. It is described as the average of the minimum noise levels measured on a sound level meter and is measured statistically as the A-weighted noise level exceeded for ninety percent of a sample period. This is represented as the LA90 noise level if measured as an overall level or an L90 noise level when measured in octave or third-octave bands.
Barrier (Noise)	A natural or constructed physical barrier which impedes the propagation of sound and includes fences, walls, earth mounds or berms and buildings.
Berm	Earth or overburden mound.
Buffer	An area of land between a source and a noise-sensitive receiver and may be an open space or a noise-tolerant land use.
Bund	A bund is an embankment or wall of brick, stone, concrete or other impervious material, which may form part or all of the perimeter of a compound.
BS	British Standard

CoRTN	United Kingdom Department of Environment entitled "Calculation of Road Traffic Noise (1988)"		
Decibel [dB]	The units that sound is measured in. The following are examples of the decibel readings of common sounds in our environment:		
	threshold of hearing	0 dB	The faintest sound we can hear, defined as 20 micro Pascal
		10 dB	Human breathing
	almost silent	20 dB	
		30 dB	Quiet bedroom or in a quiet national park location
	generally quiet	40 dB	Library
		50 dB	Typical office space or ambience in the city at night
	moderately loud	60 dB	CBD mall at lunch time
		70 dB	The sound of a car passing on the street
	loud	80 dB	Loud music played at home
		90 dB	The sound of a truck passing on the street
	very loud	100 dB	Indoor rock band concert
		110 dB	Operating a chainsaw or jackhammer
	extremely loud	120 dB	Jet plane take-off at 100m away
		130 dB	
	threshold of pain	140 dB	Military jet take-off at 25m away
dB(A)	A-weighted decibel. The A- weighting noise filter simulates the response of the human ear at relatively low levels, where the ear is not as effective in hearing low frequency sounds as it is in hearing high frequency sounds. That is, low frequency sounds of the same dB level are not heard as loud as high frequency sounds. The sound level meter replicates the human response of the ear by using an electronic filter which is called the "A" filter. A sound level measured with this filter is denoted as dB(A). Practically all noise is measured using the A filter.		
dB(C)	C-weighted decibels. The C-weighting noise filter simulates the response of the human ear at relatively high levels, where the human ear is nearly equally effective at hearing from mid-low frequency (63Hz) to mid-high frequency (4kHz), but is less effective outside these frequencies. The dB(C) level is not widely used but has some applications.		
Diffraction	The distortion of sound waves caused when passing tangentially around solid objects.		
DIN	German Standard		
ECRTN	Environmental Criteria for Road Traffic Noise, NSW, 1999		
ENMM	Environmental Noise Management Manual, Roads and Maritime Services (Transport for NSW)		
EPA	Environment Protection Authority		
Field Test	A test of the sound insulation performance in-situ. See also 'Laboratory Test' The sound insulation performance between building spaces can be measured by conducting a field test, for example, early during the construction stage or on completion. A field test is conducted in a non-ideal acoustic environment. It is generally not possible to measure the performance of an individual building element accurately as the results can be affected by numerous field conditions.		
Fluctuating Noise	Noise that varies continuously to an appreciable extent over the period of observation.		
Free-field	An environment in which there are no acoustic reflective surfaces. Free field noise measurements are carried out outdoors at least 3.5m from any acoustic reflecting structures other than the ground.		
Frequency	Frequency is synonymous to pitch. Sounds have a pitch which is peculiar to the nature of the sound generator. For example, the sound of a tiny bell has a high pitch and the sound of a bass drum has a low pitch. Frequency or pitch can be measured on a scale in units of Hertz or Hz.		

Ground-borne noise	Vibration propagated through the ground and then radiated as noise by vibrating building elements such as wall and floor surfaces. This noise is more noticeable in rooms that are well insulated from other airborne noise. An example would be vibration transmitted from an underground rail line radiating as sound in a bedroom of a building located above.
Habitable Area	Includes a bedroom, living room, lounge room, music room, television room, kitchen, dining room, sewing room, study, playroom, family room, home theatre and sunroom. Excludes a bathroom, laundry, water closet, pantry, walk-in wardrobe, corridor, hallway, lobby, photographic darkroom, clothes drying room, and other spaces of a specialised nature occupied neither frequently nor for extended periods.
Heavy Vehicle	A truck, transporter or other vehicle with a gross weight above a specified level (for example: over 8 tonnes).
IGANRIP	Interim Guideline for the Assessment of Noise from Rail Infrastructure Projects, NSW DEC 2007
Impulsive noise	Having a high peak of short duration or a sequence of such peaks. A sequence of impulses in rapid succession is termed repetitive impulsive noise.
INP	NSW Industrial Noise Policy, EPA 1999
Intermittent noise	The level suddenly drops to that of the background noise several times during the period of observation. The time during which the noise remains at levels different from that of the ambient is one second or more.
Intrusive noise	Refers to noise that intrudes above the background level by more than 5 dB(A).
ISEPP	State Environmental Planning Policy (Infrastructure), NSW, 2007
ISEPP Guideline	Development Near Rail Corridors and Busy Roads - Interim Guideline, NSW Department of Planning, December 2008
L1	The sound pressure level that is exceeded for 1% of the time for which the given sound is measured.
L10	The sound pressure level that is exceeded for 10% of the time for which the given sound is measured.
L10(1hr)	The L10 level measured over a 1 hour period.
L10(18hr)	The arithmetic average of the L10(1hr) levels for the 18 hour period between 6am and 12 midnight on a normal working day.
L90	The level of noise exceeded for 90% of the time. The bottom 10% of the sample is the L90 noise level expressed in units of dB(A).
LAeq or Leq	The "equivalent noise level" is the summation of noise events and integrated over a selected period of time, which would produce the same energy as a fluctuating sound level. When A-weighted, this is written as the LAeq.
LAeq(1hr)	The LAeq noise level for a one-hour period. In the context of the NSW EPA's Road Noise Policy it represents the highest tenth percentile hourly A-weighted Leq during the period 7am to 10pm, or 10pm to 7am (whichever is relevant).
LAeq(8hr)	The LAeq noise level for the period 10pm to 6am.
LAeq(9hr)	The LAeq noise level for the period 10pm to 7am.
LAeq(15hr)	The LAeq noise level for the period 7am to 10pm.
LAeq (24hr)	The LAeq noise level during a 24 hour period, usually from midnight to midnight.
Lmax	The maximum sound pressure level measured over a given period. When A-weighted, this is usually written as the L _{Amax} .
Lmin	The minimum sound pressure level measured over a given period. When A-weighted, this is usually written as the L _{Amin} .
Loudness	A rise of 10 dB in sound level corresponds approximately to a doubling of subjective loudness. That is, a sound of 85 dB is twice as loud as a sound of 75 dB which is twice as loud as a sound of 65 dB and so on. That is, the sound of 85 dB is four times or 400% the loudness of a sound of 65 dB.

Microphone	An electro-acoustic transducer which receives an acoustic signal and delivers a corresponding electric signal.
MPE	Moorebank Precinct East
NCA	Noise Catchment Area. An area of study within which the noise environment is substantially constant.
NCG	Noise Criteria Guideline, Roads and Maritime Services (Transport for NSW)
NMG	Noise Mitigation Guideline, Roads and Maritime Services (Transport for NSW)
Noise	Unwanted sound
Pre-construction	Work in respect of the proposed project that includes design, survey, acquisitions, fencing, investigative drilling or excavation, building/road dilapidation surveys, minor clearing (except where threatened species, populations or ecological communities would be affected), establishing ancillary facilities such as site compounds, or other relevant activities determined to have minimal environmental impact (e.g. minor access roads).
Reflection	Sound wave reflected from a solid object obscuring its path.
RING	Rail Infrastructure Noise Guideline, NSW, May 2013
RMS	Root Mean Square value representing the average value of a signal.
Rw	Weighted Sound Reduction Index A measure of the sound insulation performance of a building element. It is measured in very controlled conditions in a laboratory. The term supersedes the value STC which was used in older versions of the Building Code of Australia. Rw is measured and calculated using the procedure in ISO 717-1. The related field measurement is the DnT,w. The higher the value the better the acoustic performance of the building element.
R'w	Weighted Apparent Sound Reduction Index. As for Rw but measured in-situ and therefore subject to the inherent accuracies involved in such a measurement. The higher the value the better the acoustic performance of the building element.
RNP	Road Noise Policy, NSW, March 2011
Sabine	A measure of the total acoustic absorption provided by a material. It is the product of the Absorption Coefficient (alpha) and the surface area of the material (m2). For example, a material with alpha = 0.65 and a surface area of 8.2m2 would have $0.65 \times 8.2 = 5.33$ Sabine. Sabine is usually calculated for each individual octave band (or third-octave).
SEL	Sound Exposure Level (SEL) is the constant sound level which, if maintained for a period of 1 second would have the same acoustic energy as the measured noise event. SEL noise measurements are useful as they can be converted to obtain Leq sound levels over any period of time and can be used for predicting noise at various locations.
Sound	A fluctuation of air pressure which is propagated as a wave through air.
Sound absorption	The ability of a material to absorb sound energy by conversion to thermal energy.
Sound Insulation	Sound insulation refers to the ability of a construction or building element to limit noise transmission through the building element. The sound insulation of a material can be described by the Rw and the sound insulation between two rooms can be described by the DnT,w.
Sound level meter	An instrument consisting of a microphone, amplifier and indicating device, having a declared performance and designed to measure sound pressure levels.
Sound power level	Ten times the logarithm to the base 10 of the ratio of the sound power of the source to the reference sound power of 1 pico watt.
Sound pressure level	The level of noise, usually expressed in decibels, as measured by a standard sound level meter with a microphone referenced to 20 micro Pascal.
Spoil	Soil or materials arising from excavation activities.

SSFL	Southern Sydney Freight Line
STC	Sound Transmission Class A measure of the sound insulation performance of a building element. It is measured in controlled conditions in a laboratory. The term has been superseded by R_w.
Structure-borne Noise	Audible noise generated by vibration induced in the ground and/or a structure. Vibration can be generated by impact or by solid contact with a vibrating machine. Structure-borne noise cannot be attenuated by barriers or walls but requires the isolation of the vibration source itself. This can be achieved using a resilient element placed between the vibration source and its support such as rubber, neoprene or springs or by physical separation (using an air gap for example). Examples of structure-borne noise include the noise of trains in underground tunnels heard to a listener above the ground, the sound of footsteps on the floor above a listener and the sound of a lift car passing in a shaft. See also 'Impact Noise'.
Tonal Noise	Sound containing a prominent frequency and characterised by a definite pitch.
Transmission Loss	The sound level difference between one room or area and another, usually of sound transmitted through an intervening partition or wall. Also the vibration level difference between one point and another. For example, if the sound level on one side of a wall is 100dB and 65dB on the other side, it is said that the transmission loss of the wall is 35dB. If the transmission loss is normalised or standardised, it then becomes the R_w or $R'w$ or $D_{nT,w}$.
Wheelbase	The wheelbase is the distance between the centres of the front and rear wheels on a 2-axle bogie.